



**Radiantgreen**  
*Light For Future*

## LED DOWN LIGHT (Square)







## LED DOWN LIGHT (Square)

### RG-SDL 10W

#### Product Size




#### Photometric Curve




### RG-SDL 15W

#### Product Size




#### Photometric Curve




### RG-SDL 20W

#### Product Size



#### Photometric Curve



### Specifications

Model	RG-SDL 10W	RG-SDL 15W	RG-SDL 20W
Power	10W	15W	20W
Input Voltage	85V-265V 50/60Hz	85V-265V 50/60Hz	85V-265V 50/60Hz
Light Source	2835 SMD	2835 SMD	2835 SMD
Beam Angle	120°	120°	120°
CCT	3000K - 6500K/	3000K - 6500K/	3000K - 6500K/
Life Span	30000 Hours	30000 Hours	30000 Hours
Operation Temperature	-20°C - +50°C	-20°C - +50°C	-20°C - +50°C
Main Material	Die-Casting Aluminium	Die-Casting Aluminium	Die-Casting Aluminium
Luminous Flux	3000K-3300K	850lm ±5%	1320lm ±5%
	6000K-6500K	880lm ±5%	1720lm ±5%
CRI	3000K	≥ 70	≥ 70
	6500K	≥ 70	≥ 70
		≥ 70	≥ 70



**RADIANT TRADE SDN BHD** (875563-M)  
 Lot 1.19 & 1.20, 1st Floor Kompleks Desa, Jalan Kepong Batu 8,  
 Kepong, 52100 Kuala Lumpur, Malaysia.  
 Tel: +603.6272.1629 Fax: +603.6272.0630 Email: info@radiantgreenled.com

[www.radiantgreenled.com](http://www.radiantgreenled.com)